

Produktinformation



Information

Tillverkare	Cisco
Artnr	M9148T-PL8T=

Cisco MDS 9148T - Switch - Administrerad - 8 x 32Gb Fibre Channel SFP+ - rackmonterbar

Specifikation

Allmänt

Typ av enhet	Switch - 48 portar - Administrerad
Modell	Rackmonterbar 1U
Undertyp	Fibre Channel
Portar	8 x 32Gb Fibre Channel SFP+
Fibre Channel	FC-DA, FC-FLA, FC-FS, FC-GS-3, FC-GS-4, FC-MI, FC-PH, FC-PH-2, FC-PH-3, FC-PI, FC-PLDA, FC-SB-2, FC-SB-3, FC-SW-2, FC-SW-3, FC-Tape, FC-VI, FC-SP, FCP-4, FC-BB-2, FCP, FCP-2, FC-PI-2, FC-BB-5, FC-BB-3, FC-FS-2, FC-GS-5, FC-SW-4, FCP-3, FC-LS, FC-MI-2, FC-PI-4, FC-FS-3, FC-GS-6, FC-PI-3, FC-SW-5, FC-BB-4, FC-IFR, FAIS, FAIS-2, FC-PI-5, FC-LS-2, FC-SP-2, FC-SB-4, FC-DA-2, FC-MI-3, FC-MSQS, FC-BB-6, FC-SB-5, FC-FS-4, FC-SW-6, FC-GS-7, FC-PI-6, FC-LS-3
Nätverksprotokoll	VRRP
Protokoll för administration på distans	RMON, SNMP 3, HTTPS, SMI-S, SSH-2, CLI, SFTP
Krypteringsalgoritm	AES
Verifieringsmetod	RADIUS, TACACS+, Secure Shell v.2 (SSH2), LDAP
Funktioner	Syslog-stöd, stöd för Access Control List (ACL), Support för RSCN (Registered State Change Notification), In-Service Software Upgrade (ISSU), Fabric Configuration Server (FCS), Role-Based Access Control (RBAC), TrustSec-support, Power-on self-test (POST), Authentication, Authorization and Accounting (AAA), säker omstart, Switched Port Analyzer (SPAN), Embedded Event Manager (EEM), Anti-Counterfeit Technology, Online Health Management System (OHMS)
Statusindikatorer	System



Expansion/Anslutning

Gränssnitt	1 x 1000Base-T RJ-45 hantering 1 x 10GBase-X SFP+ hantering 1 x USB Type A 1 x seriell (RS-232) hantering 8 x 32Gb Fibre Channel SFP+
-------------------	---

Strömtillförsel

Nätdel	Intern strömförsörjning - hot-plug
Installerat antal	2 (max)
Redundant ström	Tillval
Nätspänning	AC 120/230 V (50/60 Hz)
80 PLUS-certifiering	80 PLUS Platinum

Diverse

Standarder som följs	CISPR 22 klass A, EN 60950, EN 61000-3-2, IEC 60950, EN 61000-3-3, EN55024, UL 60950, EN50082-1, EN 61000-6-1, AS/NZS 3260, EMC, ICES-003 klass A, EN 60825, AS/NZS 3548 klass A, IEC 60825, CAN/CSA C22.2 No. 60950, VCCI Class A, EN 55022 Class A, FCC CFR47 Part 15 A, 21 CFR 1040, TS001
-----------------------------	---

Dimensioner och vikt

Bredd	43.9 cm
Djup	56.6 cm
Höjd	4.37 cm
Vikt	8.5 kg

Tillverkarens garanti

Service och support	Begränsad garanti - utbyte av delar i förväg - 1 år - svarstid: 10 dagar
----------------------------	--

Miljöparametrar

Min temperatur vid drift	0 °C
Max temperatur vid drift	40 °C
Luftfuktighet vid drift	10 - 90 % (icke-kondenserade)
Min temperatur vid förvaring	-40 °C
Max temperatur vid förvaring	70 °C
Luftfuktighet vid lagring	10 - 95 % (icke-kondenserande)