



Produktinformation



Information

<i>Tillverkare</i>	Leadtek Research
<i>Artnr</i>	TERA2321-DP-DVI-RJ45

TERA2321 DP+DVI Zero Client (RJ45 edition) incl. 1 year Teradici Desktop Access

Specifikation

Orderable item, expected delivery time approx. 3-5 days. TERA2321 Series Max Number of Displays 2 Processor TERA2321 Imaging Performance 50 Mpps (VDI) 130 Mpps (Workstation)* Maximum Resolution One 3840x2160 (DP model only)*** One 2560x1600 Two 1920x1200 Memory Type Device Physical Dimensions 5.91 (height) x 5.12 (length) x 1.77 (thinness) inches Contact us for details on our enclosures and their dimensions Power Management Full Wake-on-LAN and Wake-on-USB Typical Device Power 6W Encryption AES-128/AES-256 Suite B Ciphers (Workstation) Connectors Single-link DVI-D or DisplayPort connector Second Single-link DVI-I connector (or One Dual-link DVI-D with adapter) Two or four front USB 2.0 connectors** Two rear USB 2.0 connectors Smart Card Reader port (Optional) Headphone jack Microphone jack Speaker jack (for Dual-DVI zero clients) RJ45, RJ45 with PoE (Power-over-Ethernet), or Fiber Ethernet connector 12VDC Power jack LED PCoIP LED Zero Client Power Button LED Button Zero Client Power Button Thermal Cooling Solution Passive heat sink Operating System Support Completely operating system independent Package Content PCoIP Zero Client Power adaptor and power cord Ethernet cable (Optional) Dual-link DVI adapter cables (Optional for TERA2140 Quad-DVI and TERA2321 Dual-DVI zero clients)*** Quick installation guide VESA mount package (Optional)