



## Produktinformation

### Information

<i>Tillverkare</i>	Option Wireless Technology
<i>Artnr</i>	GI0505-11541

## Icon 505 USB 10,2 HSDPA+ 5,76 HSUPA/Edge/ GPRS/GSM

## Specifikation

Specifications •HSUPA/HSDPA/UMTS Air Interface •WCDMA 900/2100\* MHz > Release 6 compliant •HSDPA Category 10 (14.4Mbps) \*\* •HSUPA Category 6 (5.76Mbps) •UE Power Class 3 EDGE/GSM Air Interface •850/900/1800/1900 MHz •EDGE Power Class E2, GSM Power Class 1 at 1800/1900 Mhz and Power Class 4 at 850/900 Mhz •Coding scheme UL & DL - CS 1-4, MCS 1-9 •Packet-switched data •Multislot (E)GPRS Class 12, (E)GPRS Class B Type 1 MT •Streaming, Background and Interactive QoS Classes Supported •Terminal Equipment Interfaces •Drivers: Windows ®XP (Pro & Home), Windows Vista® 32/64bit, Mac OS X and Linux •SIM-ME interface as specified in 3GPP >>GSM TS11.11 and GSM 11.12 with compliance to ISO 7816 •SIM application toolkit support •NDIS or Standard modem emulation for com>>patibility with terminal programs/diallers and for use with proprietary operating systems. AT Interface 3GPP TS27.005, ATD\*99# and ATD\*99\*\*\*<CID># support •Multiple communication ports for simultaneous >>data call and network coverage reports •Single, green LED •Supporting 1.8 and 3V UICCs •SIM card interface compliant with 3GPP >>31.101 and 31.102 •USB 2.0, backward compatible to USB 1.1 >> •118MB of memory for operator applications >>and files \*RX Diversity \*\*Might be shipped in lower speed configuration, depending on operator network capabilities Software •All applicable regulatory approvals, Operator >>and Infrastructure IOT •Microsoft WHQL certified drivers Environmental •Operating temperature -10 to +55°C •RoHS Compliant